

SD722W

Speaker Package

Installation Instructions

1. Use two wire nuts to attach the appropriate transformer wires to the field wiring.
See the charts to the right for wire color tap selection.
2. Cut off the bare portion of the unused leads and terminate with wire nuts.

Hardware Reference

Model SD722W mounts to all Atlas Sound 8" baffles except for the FA Series.

Model SD722W is compatible with the following Atlas Sound hardware items:

Mounting Rings	75-8, 76-8E2, P77-8, & P78-8
T-Bridges	81-8R & 81-8S
Enclosures	(EZ)95-8 Series, Q408, CS95-8, BMT95-8, & BMT95-8-7

Specifications

Frequency Response	55Hz – 8kHz
Sensitivity	97dB (1W/1M)

Tap Wattage	70.7V
0.25	Red
0.5	White
1	Yellow
2	Blue
COMMON	BLACK

Tap Wattage	25V
0.25	Brown
0.5	Green w/ White
1	Violet
2	Orange
COMMON	BLACK



©2009 Atlas Sound L.P. All rights reserved. Atlas Sound is a trademark of Atlas Sound L.P. All other trademarks are the property of their respective owners. All specs are subject to change without notice. ATS003737 RevA 11/09



1601 JACK MCKAY BLVD.
ENNIS, TEXAS 75119 U.S.A.

TELEPHONE: (800) 876-3333
FAX: (800) 765-3435

AtlasSound.com