

1112 PSD

GLOBALCOM Modular Power Supply



Features

- Small modular design
- Provides 12V DC to individual GLOBALCOM devices
- Internal current limiting to prevent equipment damage
- Over voltage
- Efficiency > 81% at full load
- Universal input voltage for worldwide use

General Description

The 1112PSD is a small modular power supply designed to provide 12V DC power to individual GLOBALCOM devices. The 1112PSD is included as the default power module for the IED1100, IED1200, IP100 and IED1100DAB series devices. The module is capable of delivering up to 4 Amps of 12V DC power to a single GLOBALCOM device. The small form factor for a variety of mounting options for the module.

Specifications

Electrical	
Supply Voltage	100 - 240 VAC (50 - 60Hz)
Rated Input Current	1.2 Amps Max
Rated Output Voltage	+ 12VDC (±1%)
Rated Output Current	2 Amps
Mechanical	
Height	1.5" (3.8 cm)
Width	2.4" (6.0 cm)
Depth	4.7" (12.0 cm)
Weight	10.9 oz. (310g)
Environmental	
Operating Temperature Range	32° F - 113° F (0° C - 45° C)
Storage Temperature Range	-4° F - 185° F (-20° C - 85° C)
Connectors	
Input	IEC 60320 Type C-13
Output	2-pin Phoenix, 3.81mm spacing with locking screws
Compliance	
UL Listed	

©2021 Atlas Sound L.P. The Atlas "Circle-A", Soundolier, and Atlas Sound are trademarks of Atlas Sound L.P. IED is a Registered Trademark of Innovative Electronic Designs LLC. All rights reserved. All other Trademarks are property of their respective owners. No endorsement is implied. Due to continual product development, specifications are subject to change without notice. ATSO06871 RevA 12/21