

SW118AC/SW118XC

18" Active/Passive Subwoofer System



SW118AC-B

Features

- Single 18" Subwoofer
- NL4 and Barrier Strip Terminal Connectors
- Also Available in White
- Configurable DSP via Software(Active Version)
- AES Input(Active Version)

Application

The A-Line subwoofer system is ideal for use in medium and large venues where excellent bass of speech or live music reproductions is required.

- Houses of Worship
- Medium Music Venues
- Medium Auditoriums
- Lecture Halls
- Meeting Rooms

General Description

The AtlasIED SW118 is a single 18" subwoofer model designed to work in conjunction with an EJ2003 or EL1503 in applications where more bass is required. The SW118XC is designed to work in systems using the SW118AC powered subwoofer system. The onboard amplifier in the SW118AC provides amplification for the passive driver in the SW118XC. Each unit is finished in heavy duty black. The SW118XC is also available in white finish, model SW118X-W.

Specifications

Subwoofer	SW118AC	SW118XC
Loudspeaker Power	500W	500W
Impedance	8Ω	8Ω
Frequency Response	40Hz – 125Hz	40Hz – 125Hz
Driver	1x 18"	1x 18"
Amplifier		
Power	2x900Watts@8Ω	NA
THD+N	≤0.05%	
S/N rate (A)	≥100dB	
Damping factor	≥2000	
Conversion rate	≥10 V/μS	
DSP	EQ Filters/Noise Generator/Delay/High & Low Pass Filter/Limiter/Temp/10 Preset	
Connector		
	I/O PowerCON™	2x NL4
	M&F XLR	2x Barrier Terminal
	1x USB	
	2x NL4	
	2x Barrier Terminal	
Dimensions		
Height	24.8" (63cm)	24.8" (63cm)
Width	20.86" (53cm)	20.86" (53cm)
Depth	22.44" (57cm)	22.44" (57cm)
Weight	84 lbs (38.1kg)	76 lbs (34.5kg)