

ELIJAH

Active, Medium Length Line Array with Subwoofer



Features

- EJ2003 Full Range Speaker System
 - Twenty 3" Proprietary Full Range Speakers
 - Pattern Control to 200Hz
 - EJ2003C is Pole Mount on Top and Bottom for Stacking
 - EJ2003IC is Fixed Install (Bracket for sale separately)
- EJW115AC / EJW115XC Subwoofer System
 - Single 15" Low Frequency Driver
 - Available With or Without Integrated Amplifier
- Birch Sealed Cabinet Construction
- Finished in Heavy Duty Black Duracoat™

Application

The A-Line ELIJAH system is ideal for use in small venues where excellent speech or live music reproductions is required.

- Houses of Worship
- Medium Music Venues
- Medium Auditoriums
- Lecture Halls
- Large Meeting Rooms

General Description

The AtlasIED A-Line ELIJAH Line array speaker system is a highly intelligible, high efficiency speaker system that is ideally suited for use in speech and music reproduction applications for small venues such as houses of worship, medium sized theaters, and schools. The system consists of two parts: the EJ2003, which includes twenty proprietary 3" drivers, and the EJW115, which is a single 15" low frequency driver. Both models utilize an optimally designed birch constructed enclosure. The EJW115AC houses an integrated class D amplifier that includes onboard DSP. The EJW115AC is designed to provide power to the EJW115XC and the two EJ2003 arrays. The trim line, two cabinet design allows for sleek, clean looking set ups with minimal sightline interference. This kit includes everything needed to set up the system, including the power cable, speaker cables and poles.

Specifications

Line Array	EJ2003C / EJ2003IC	
RMS Power	500 Watts	
Impedance	8Ω per Cabinet	
Max SPL	121dB	
Frequency Response	125Hz – 16kHz	
Drivers	Twenty (20) 3"	
Connector	2x NL4 / 1x Barrier Terminal	
Dimensions		
Height	65.6" (166.6cm)	
Width	4.8" (12.2cm)	
Depth	6.4" (16.2cm)	
Weight	56 lbs (25.4kg)	
Subwoofer	EJW115AC	EJW115XC
Amplifier Power	2x900Watts@8Ω	NA
Impedance	8Ω	8Ω
Frequency	41Hz – 140Hz	41Hz – 140Hz
Response Driver	1x 15"	1x 15"
Connector	I/O PowerCON™ M&F XLR USB 2x NL4 2x Barrier Terminal	2x NL4 2x Barrier Terminal
Dimensions		
Height	21.6" (54.86cm)	21.6" (54.86cm)
Width	18.25" (46.36cm)	18.25" (46.36cm)
Depth	19.4" (49.28cm)	19.4" (49.28cm)
Weight	78.48 lbs (35.6kg)	70.54 lbs (32kg)